









VZ-10 & VZ-18

COST EFFECTIVE PTT TWO-WAY COMMUNICATION

UHF/VHF PORTABLE RADIO

The VZ-10 and VZ-18 radios are cost effective communication tools meant for both first time and intermediate users. These portable radios are equipped with the necessary features to ensure reliable communication at an affordable price.

COMPACT AND DISCREET

The compact and discreet size of the VZ Series allows users to seamlessly integrate the radio into existing business operations comfortably.

SIMPLE AND RELIABLE

The VZ-10 and VZ-18 radios are easy to use and are reliable so you are always in contact with your team.

NEVER MISS A CALL

Scan and Priority Scan options allow you to programme and configure your radios to skip channels, letting you communicate quickly using the right channel.

CHANNEL ANNOUNCEMENT

Upon channel switching, the radio announces the current channel. Users can toggle between channels without having to look at the radio, thus improving work productivity.

LOUD AND CLEAR AUDIO

The 1-Watt speaker ensures important communications are heard even in noisy environments

EASY TO PROGRAMME CHANNELS

For the VZ-18 model, up to 128 channels can be stored either through programming software, or via the front panel.

LI-ION BATTERY SOLUTIONS

Up to 10 hours of talk time allows you and your team to get through a shift without worrying about running out of power.

2-PIN CONNECTOR ACCESSORIES

The 2-pin side connector enables standard audio accessories to be used, helping reduce your overall cost of ownership.



VZ-18





| | VZ-10 | | VZ-18 | |
|--|---|-------------|---|-------------|
| | VHF | UHF | VHF | UHF |
| Frequency Range | 136-174 MHz | 400-470 MHz | 136-174 MHz | 400-470 MHz |
| Number of Channels | 16 channels | | 128 channels | |
| Power Supply Voltage | 7.2 V DC | | 7.2 V DC | |
| Channel Spacing | 25/12.5 kHz | | 25/12.5 kHz | |
| Battery Life (5-5-90 duty cycle with 1600mAh battery): | 10 Hours (With battery saver)/ 8 Hours (Without battery saver) | | 10 Hours (With battery saver)/ 8 Hours (Without battery saver) | |
| IP Rating | IP54 | | IP54 | |
| Operating Temperature Range | -25° C to +60° C | | -25° C to +60° C | |
| Frequency Stability | ±2.5 ppm | | ±2.5 ppm | |
| RF Input-Output Impedance: | 50 ohm | | 50 ohm | |
| Dimension (H x W x D) | 126 x 61 x 39 mm with FNB-Z165LI | | 126 x 61 x 39 mm with FNB-Z165LI | |
| Weight (Approx.) | 250g (With battery, antenna, belt clip) | | 260g (With battery, antenna, belt clip | |
| RECEIVER SPECIFICATIONS | | | | |
| Sensitivity (12dB SINAD): | 0.22uV | | 0.22uV | |
| Adjacent Channel Selectivity (25/12.5 kHz) | 65 / 60 dB | | 65 / 60 dB | |
| Inter-modulation Rejection: (25/12.5 kHz) | 58 dB | | 58 dB | |
| Spurious Image Rejection | 65 dB | | 65 dB | |
| Audio Output | > 800mW @ 16 0hms (INT) | | > 800mW @ 16 0hms (INT) | |
| TRANSMITTER SPECIFICATIONS | | | | |
| Output Power | 5/1 Watt | 4/1 Watt | 5/1 Watt | 4/1 Watt |
| Modulation | 11КФF3E 12.5kHz,16КФF3E 25kHz | | 11КФF3E 12.5kHz,16КФF3E 25kHz | |
| Conducted Spurious Emission | -30dBm for 9KHz 1GHz, -30dBm for >1GHz | | -30dBm for 9KHz 1GHz, -30dBm for >1GHz | |
| FM Hum and Noise (25/12.5 kHz) | 40 / 35 dB | | 40 / 35 dB | |
| Audio Distortion | < 5% | | < 5% | |

ADDITIONAL FEATURES

- Battery Status Indicator
- Battery Saver Mode
- Talkaround
- ▼ CTCSS/DCS Encode/Decode
- Channel Announcement
- Internal VOX (Voice Activated Transmit)
- 2-pin accessory connector
- Busy Channel Lockout (BCLO)
- ▼ PTT ID
- Keypad Lock (VZ-18 only)

ACCESSORIES

- CZ084AUA61 MHZ-101B Remote Speaker Microphone
- CZ084AUA62 MHZ-201B Inline PTT Earbud
- CZ084AUA63 MHZ-202B G-Hook Earbud
- CZ073CB601 CZ-113 VZ-10/18 Series Programming Cable
- CZ089AN601 UHF Antenna 400-470 MHz
- CZ089AN602 VHF Antenna 136-174 MHz
- CZ089B601 FNB-Z165 Li-lon 1600mAh Battery
- CZ089C601 CV13 Charger Base
- CZ083P603 PV-05C Power Adaptor, EU 2 pin
- CZ083P604 PV-05U Power Adaptor, UK 3 pin
- CZ072CL61 Belt Clip VZ Series (for FNB-Z165LI)

